

D150



Power over Ethernet (PoE)



Gigabit Ethernet



IPv6 & IPv4



Headset connectable



Security (TLS & SRTP)



SmartLabel



HD audio



OpenVPN

For more comfort in your daily work

Finished in slate grey and with an uncluttered design, the D150 fits perfectly into any work environment where phone communication is paramount. It combines the latest technology and the best voice quality at an unbeatable price. The D150 feels at home wherever efficiency and optimum costs are

required. The highly visible, backlit LED display makes it easy to monitor information on calls and features. The D150 is equipped with a gigabit switch with PoE support and an RJ9 headset port.

Basics

- Product information
 - IP desk phone D140 | slate gray | PN 00004652
 - Operating system: Linux
- Placement: indoor, desktop, wall mounting¹

Dimensions and weight

- Dimensions (L × W × H, approx.) without footstand
 - 205 mm × 185 mm × 40 mm
- Dimensions (H × W × D, approx.) with footstand
 - 205 mm × 185 mm × 220 mm (high angle 46°)
 - 205 mm × 185 mm × 200 mm (low angle 28°)
- Weight (approx.):
 - 710 g without footstand
 - 830 g with footstand

Display and indicators

- Display
 - TFT liquid crystal display (LCD): graphical, grayscale, backlit
 - Size (diagonal): 2.8" (67 mm)
 - Size (W × H): 59 mm × 33 mm
 - Resolution: 320 × 240 pixel
- 3 LED indicators
 - Call status indication: 1 red LED
 - Function key status indication: 2 multicolour LEDs

Keypad and function keys

- 36 hard keys in total
 - 12 keys (standard ITU telephone keypad)
 - 4 context-sensitive function keys
 - 5-way navigation key
 - 2 SmartLabel keys (with multicolour LED)
 - 5 dedicated audio keys
 - Mute
 - Speakerphone
 - Headset
 - Volume + / - (rocker)

- 8 dedicated function keys
 - Ok
 - Cancel
 - DND
 - Message (with red LED)
 - Directory
 - Menu
 - Transfer
 - Hold
- Keyboard lock

Audio devices, codecs and features

- Casing microphone | Casing speaker
 - Speakerphone mode: Full duplex
- Corded handset
 - Microphone | Handset earpiece
 - Hearing aid compatible (HAC)
- Audio codecs
 - G.711 (A-law, μ -law), G.722, G.726, G.729, GSM 6.10 (FR)
- Dual-tone multi-frequency signalling (DTMF / RFC2833)
 - SIP-INFO
 - in-band
 - out-of-band
- Related features
 - Built-in assignable ringtones
 - Comfort Noise Generator (CNG)
 - Voice Activity Detection (VAD)

Interfaces and connections

- Power options
 - [Power over Ethernet \(PoE\)](#)
 - [IEEE 802.3af, class 1](#) | [IEEE 802.3az](#)³
 - Power adapter¹
 - 100 - 240 V AC, 50 - 60 Hz | 5 V DC (SELV), 2 A, 10 W
- Wired interfaces
 - Power adapter:¹ coaxial power connector (socket)
 - Network connectivity: 2 × RJ45-8P8C (NET/PC) sockets → Gigabit Ethernet (GbE)
 - Corded handset: RJ9-4P4C socket
 - Headset:¹ RJ9-4P4C socket
 - [EHS adapter](#):¹ RJ12-6P6C (EHS) socket
- Sensors
 - Hook switch sensor

User interfaces and setup

- [Configuration and setup via menu-driven web user interface \(WUI\)](#)
 - Password-protected login
 - Secure web server/client (HTTPS)
- [Configuration and setup via menu-driven phone user interface \(PUI\)](#)
- Customisation: [XML browser](#)
- [Automatic configuration via provisioning](#)
 - Loading of settings and firmware via HTTP, HTTPS, TFTP
 - Supported DHCP provisioning options [66](#) / [67](#)
 - [Secure Redirection And Provisioning Service \(SRAPS\)](#) support
 - Plug & Play (PnP) support
 - [Remote management via TR-069 / TR-069 Annex G \(TR-111\)](#)
- Localization
 - [Languages](#)
 - Time zone, dial tone
- Diagnostic
 - SIP / PCAP trace

- Syslog

Networking technologies and protocols

- Network technologies
 - [OpenVPN](#), [VLAN \(IEEE 802.1q\)](#)
- VoIP related protocols and techniques
 - [SIP](#), [SDP](#), [RTP](#), [RTCP](#), [RTCP-XR](#), [SIP REFER method \(RFC 3515\)](#), [rport \(RFC 3581\)](#), [ENUM](#), [ICE](#), [STUN](#)
- Secure VoIP protocols
 - [SIPS \(SIP over TLS\)](#), [SRTP](#), [SRTCP](#)
- Network protocols
 - IPv4 / IPv6 (dual stack), [DHCP](#), [NTP](#), [LDAP](#), [LLDP-MED](#), [HTTP](#), [TFTP](#), [L2TP](#)
- Secure network protocols
 - [TLS V1.2](#), [HTTPS](#), [IEEE 802.1X \(EAPoL\)](#)
- Remote management protocols
 - [TR-069](#), [TR-069 Annex G \(formerly TR-111\)](#)

Interoperability

- Certified VoIP partner

Directory support and call features

- 2 SIP identities / accounts
 - Up to 2 simultaneous calls
- Directory support
 - LDAP (server-based directory)
 - Local directory with up to 1,000 entries
- Outgoing call features
 - Speed dialling via function keys
 - URL dialling
 - Local dial plan
 - Redial (via dialed calls list)
 - Automatic redial on busy
 - Caller identification (CLIP)
 - Calling Line Identification Restriction (CLIR)
 - Call completion (busy/unreachable)²
 - Intercom
 - Multicast paging
- Incoming call features
 - Call waiting/swapping
 - Call barring/blocking: deny list, anonymous calls, Do Not Disturb (DND) mode
 - Auto answer
 - Call diversion
- Connected call features
 - Mute microphone
 - Hold
 - Music on hold²
 - Blind call transfer
 - Attended call transfer
 - 3-way local conferencing
 - Call park / unpark²
 - Client Matter Code (CMC)²
- Related features
 - Call history lists of missed, received, dialed, rejected, and deflected calls
 - Extension monitoring (Busy lamp field), call pickup²

Environmental conditions

- Operating ambient temperature: 0 °C - +35 °C
- Nonoperating (storage) temperature: -10 °C - +45 °C
- Humidity (non-condensing): 5 % - 95 %

Package contents

- Hardware
 - IP desk phone D150
 - Footstand
 - Corded handset
 - Ethernet cable
- Documentation
 - [Quick Installation Guide](#)

- [GNU General Public License](#)

Snom accessories and compatible devices

- Power adapter
 - [Snom 10 W PSU \(PN 00004570\)](#)
- EHS adapter
 - [EHS Advanced 2.0 \(PN 00002362\)](#)
- Wired headset via RJ9-4P4C
 - Binaural: [A100D \(PN 00004342\)](#), [A310D \(PN 00004626\)](#)
 - Monaural: [A100M \(PN 00004341\)](#), [A310M \(PN 00004624\)](#)
- DECT headset via RJ9-4P4C
 - [A170 \(PN 00004387\)](#)



10 W PSU



EHS 2.0



A100D



A100M



A310M



A310D



A170

¹ Available separately

² If supported by PBX

³ Optional via software

Series overview



D120



D140



D150

Disclaimer

Further information : [Snom D150 webpage](#) | [Snom Service Hub](#) | [Type approval](#) | [Warranty information](#) | [Company locations](#)

Snom, the names of Snom products, and Snom logos are trademarks owned by Snom Technology GmbH. All product specifications are subject to change without notification. Snom Technology GmbH reserves the right to revise and change this document at any time, without being obliged to announce such revisions or changes beforehand or after the fact. Although due care has been taken in the compilation and presentation of the information in this document, the data upon which it is based may have changed in the meantime. Snom therefore disclaims all warranties and liability for the accurateness, completeness, and currentness of the information published, except in the case of intention or gross negligence on the part of Snom or where liability arises due to binding legal provisions.