

# 2N® INDOOR VIEW

ANSWERING UNIT WITH FULL SCREEN VIDEO

The main benefit of the 2N® Indoor View answering unit is a 7" touchscreen with wide viewing angle. The unit's tempered glass surface and award-winning design perfectly match any luxury residential project. To install the device, all you need is a UTP cable and an installation box. Our custom operating system is your guarantee that the unit will operate reliably and simple configuration.



- **7" HD touchscreen**
- **Full screen video calls**
- **Award-winning design**
- **Residents' privacy in safe hands**
- **First configuration from the convenience of your office**
- **Produced and developed in Europe**

## VARIANTS



### BLACK

91378601



### WHITE

91378601WH

## TECHNICAL PARAMETERS

### Power supply

Type	12 V / 1 A DC or PoE
PoE	802.3af
Reverse polarity protection	Yes

### User interface

Controls	capacitive touch panel
Operation	Press and hold the RESET button to restore factory settings, 3 LED status indicators

### Audio

Microphone	Integrated
Speaker	Integrated, 2W
Induction loop output	600 mV RMS
Codecs	G.711, G.722, G.729, L16/16kHz

### Video

Display	7" display, resolution 1024x600 pixels
Codecs	H.264, MJPEG

### Interface

LAN	10/100BaseT, RJ-45
Recommended cabling	Cat5e or higher

### Doorbell Input

Input type	Switching contact (button/relay)
Contact type	Normally open (NO)
Contact parameters	Up to 50V/5mA, DC

### Mechanical properties

Operating temperature	0 to 50°C
Storage temperature	-20 to 70°C
Relative operating humidity	10 to 90 % (non-condensing)
Recommended altitude	0 to 2000 m
Dimensions (W x H x D)	193 x 157 x 50mm
Weight	555g

) - ??- ; AF F2- ?@D - ??- ; AF @22 5AA=@ DDD ; 0<: 2; ~ ~ @B==<?A D - ??- ; AF - ; 1 ?2=- 6@