



## Auteldac 4

### ATEX Approved Hazardous Area Telephone



- **Ex II 2 G ATEX certified telephone**
- **CE (R&TTE Directive 1999/5/EC and ATEX Product Directive 94/9/EC)**
- **IEC Ex certified, GOST Approved**
- **Fully compliant with TBR21 / TBR38**
- **Full keypad with 3 programmable memory buttons, or CB variant**
- **Headset Option**
- **90dB sounder (adjustable)**
- **Secondary beacon / external sounder actuator**
- **Robust and weather resistant up to IP66**
- **Industry standard robust handset c/w curly cord or armoured stainless steel**
- **Noise cancelling versions available**
- **Dual purpose design for wall or desk mounting, simple installation**

The Auteldac 4 (A4) telephone has secured ATEX approval to provide a tough, weather resistant unit built to withstand arduous industrial atmospheres and environmental extremes.

Certified for safe operation in hazardous areas, the Auteldac 4 body is made from carbon loaded glass filled polyester to eliminate rust and corrosion. The handset has a choice of armoured stainless steel or curly cords.

The elimination of moving parts maintains a high level of reliability to industrial and weather resistant telephones.

Features such as 'electronic on-hook sensing' and 'electronic tone ringer' enable an enclosure protection up to IP66. Should the handset be left off-hook, the A4 will automatically revert to on-hook state after a period of 6-8 minutes (this option can be disabled).

Auteldac 4 telephones come complete with an integral ringer with volume control and secondary beacon / external sounder actuator as standard. An inductive coupler is fitted to aid the hard of hearing.

For hands-free telephone use, the Auteldac 4 has the option of a headset.

**Connectivity:**

**Standard Analogue**

The standard analogue unit provides basic telephone functions and can be connected to any standard two-wire telephone line, including FXS ports, analogue PABX lines and PSTN.

**Keypad Options:**

**18 button Full Keypad**

Included in the 18 button version, are 3 direct dial buttons for fast one touch dialling of pre-stored numbers or accessing low cost call facilities. Includes: **M1- M3** Memory buttons, **S** 'Store', **R** 'Recall', **LR** 'Last number redial'

**0 button CB**

This can be used to initiate a PABX 'hotline' or lift handset and wait for reply, where the PABX does the call routing/dialling. Autodial on handset lift also available.



#### TECHNICAL SPECIFICATIONS (please refer to technical manual for full product details)

##### Enclosure:

Carbon loaded glass-filled polyester (colour: black)

**Surface resistance:**  $<10^9$  ohms

##### Handset:

Conductively coated polycarbonate handset with coiled cord or stainless steel spiral cord. Noise cancelling options available. Extended cord lengths available.

##### Keypad:

Weathersealed tactile digital keypad

##### Hookswitch:

Electronic with no mechanical moving parts

**Degree of protection:** Up to IP66

**Ringing:** Shrill warble tone  $>90$  dBA @ 1 metre typical. Internal volume control.

**Power Supply:** Drawn from telephone line

##### Integral Ring Detector:

Contact closure following the ringing cadence, rated at 250Vac, 5A.

##### Isolated hookswitch sensor:

Additional contact rated at 250Vac, 150mA

##### Parallel Terminal Block:

Duplicated line terminals allows connection to a parallel device without an additional junction box.

##### Time Out:

Enforces a fixed call maximum time limit to 6-8 minutes from lifting of the handset. User selectable.

##### Dialling system:

LD or DTMF (switchable)

##### Recall Button:

Internally switchable from Earth Loop Recall (600ms pulse) and Timed Break Recall 98ms, 250ms or 604ms.


##### Certified Operating Temperature:

$-20^{\circ}\text{C}$  to  $+50^{\circ}\text{C}$  ( $-40^{\circ}\text{C}$  to  $+50^{\circ}\text{C}$  for GOST)

**Relative Humidity:** Up to 95% (non-condensing)

**Weight:** approx. 3.1 kg

#### DIMENSIONS:



#### ORDER CODE

##### Auteldac 4 Curly Cord

18btn standard unit	212-02-2008-031
18btn + headset socket*	212-02-2008-231
CB standard unit	212-02-2000-031
CB + headset socket*	212-02-2000-231


##### Auteldac 4 Stainless Steel Cord

18btn standard unit	212-02-2008-020
18btn + headset socket*	212-02-2008-220
CB standard unit	212-02-2000-020
CB + headset socket*	212-02-2000-220

##### Headset & Plug for Auteldac 4

*Headset and plug	100-02-0598-001
Extension Cord for Headset	610-35-2036-001

#### CONNECTION OPTIONS



#### APPROVALS

##### Telephone compliance

Ex II 2 G EEx e m ib IIC T5 ( $-20^{\circ}\text{C} \leq T_a \leq 50^{\circ}\text{C}$ ) Baseefa03ATEX0617

IECEX BAS 05.0060 Ex e mb ib IIC T5 ( $-20^{\circ}\text{C} \leq T_a \leq 50^{\circ}\text{C}$ )

GOST Approval (Russia) **POCC GB.Г506.В00377** ( $-40^{\circ}\text{C} \leq T_a \leq 50^{\circ}\text{C}$ )

##### Headset compliance

Ex II 2 G EEx ib IIC T4 ( $-20^{\circ}\text{C} \leq T_a \leq 40^{\circ}\text{C}$ ) TUV03ATEX2124

GOST Approval (Russia) **POCC GB.Г506.В00377** ( $-40^{\circ}\text{C} \leq T_a \leq 40^{\circ}\text{C}$ )

**CE** This mark indicates compliance with the following directives:  
R&TTE Directive 1999/5/EC, ATEX Product Directive 94/9/EC, Tested to TBR21 / TBR38

The GAI-Tronics Quality Management System has been approved by LRQA to ISO9001:2000 & ISO 14001:2004. Certificate No. 861888

