

MITEL MiVOICE 8568 TELEPHONE

ULTIMATE TECHNOLOGY – PROFESSIONAL PRODUCTIVITY



Compatible with the Mitel MiVoice Office (formerly Mitel 5000 Communications Platform), the Mitel MiVoice 8568 Telephone is perfect for users who require efficient call processing capabilities.

This powerful digital telephone features a six line x 16 character display with eight menu-driven softkeys, which intuitively guide users through system features and capabilities. The ideal small or medium business phone, the MiVoice 8568 Telephone has a large message waiting lamp in the upper right hand corner that is visible from all angles, 16 programmable keys with LED indication and 10 function keys that allow one-touch operation for the most commonly used telephony functions or settings. Equipped with both speakerphone capability and a dedicated headset jack, the MiVoice 8568 Telephone is designed to enhance productivity.

UNIFIED COMMUNICATIONS SUPPORT

When used with Mitel Unified Communicator® (UC) Express or Mitel MiCollab Client (formerly Mitel Unified Communicator® (UC) Advanced) applications, the MiVoice 8568 Telephone becomes a powerful communications tool that helps customers streamline communications between people and organizations. This leads to improved productivity, enhanced customer service, reduced costs, and ultimately improved business process integration.

SCALABLE FUNCTIONALITY

The MiVoice 8568 Telephone integrates with the Mitel Programmable Key Module (PKM) 12 and Mitel Programmable Key Module (PKM) 48 for easy addition of quick access function keys.

FEATURES

- Six-line x 16-character alphanumeric display with eight, menu-driven, context-sensitive softkeys
- 16 programmable multi-function keys with LED indicators
- 10 hard function keys: Mute, Speaker, Volume Up / Down, Directory, Feature, Redial, Hold, Transfer, Message
- Support for optional 12 and 48 button Programmable Key Modules
- Hands-free operation (half-duplex)
- Dedicated headset jack
- Speed Calling (System / Station)
- Intercom Calling
- Emergency Calling
- Call Hold (Place / Retrieve)
- Call Transfer
- Conference Calling
- Call Waiting
- Do Not Disturb
- Call Forward (Manual / Automatic)
- Voice mail notification – large message waiting lamp
- Message handling (View / Reply)
- Direct page / Group page
- Group Listen
- Last number redial
- Reminder Messages
- Call Logging (up to 20 entries)
- Store up to 10 station (personal) Speed Dial numbers
- Hearing Aid Compatible handset
- Wall mountable
- Two-position, 35 degree tilting stand for better viewing angle
- 12-button Alpha / Numeric Dial Pad
- Easily customize Do-Not-Disturb (DND) messages such as "In a meeting until 2:00," "Leave a message" or "On Vacation Until"

ADVANCED FEATURES

- Adjust Volume Levels: Provides multiple levels of volume for speaker, ringer, handset and headset
- Select a Ring Tone
- Enable Background Music
- Enable Automatic Call Answer
- Change the Display Language
- Return Phone to Default Operation
- Use Record-A-Call
- Enable Paging
- Place a Page Announcement
- Program Feature Buttons
- Program Direct Station Select (DSS) Keys
- Program Secondary Extension Keys
- Use Accounting Codes
- Enter a Remote Access Password
- Remote Feature Access

SYSTEM REQUIREMENTS

- MiVoice Office – Release 3.2 or higher (formerly Mitel 5000 Communication Platform (CP))

TECHNICAL SPECIFICATIONS

MAXIMUM LOOP LENGTH

1,200 ft (366 meters)

ENVIRONMENTAL

OPERATING TEMPERATURE	OPERATING HUMIDITY	STORAGE TEMPERATURE	STORAGE HUMIDITY
+4°C to +49°C	34% at +49°C, 95% at 29°C	-40°C to +70°C	15% at +70°C, 95% at 29°C

REGULATORY APPROVALS

EMC	SAFETY	TELECOM
CANADA: ICES-003 (CLASS B) USA: CFR TITLE 47, PART 15 (CLASS B) EUROPEAN UNION: EN55024: 1998 + A1: 2001 + A2:2003 EN55022: 2006 + A1: 2007 (CLASS B) EN 61000-3-2: 2006 EN 61000-3-3: 1995 + A1: 2001 + A2: 2005 EN 61000-4-2: LEVEL 4	CANADA: CSA C22.2 NO. 60950-1 USA: UL 60950-1-07, Second Edition ANSI / NFPA 70, "National Electrical Code" EUROPEAN UNION: EN 60950: 2006	CANADA: CS03 Part V (hearing aid compatible) USA: FCC Part 68 (CFR 47) (Hearing Aid Compatible) US Americans with Disabilities Act (ADA) (HAC and Volume Control)

TELEPHONY

POWERING PHONE RATE	PKM	CONSUMPTION	SIZE (L X W X H)	WEIGHT	MTBF
Line powered from the digital loop interface	Output: 24 Vdc Input: 110 V 50-60 Hz 220 V 50 Hz	1 W	9.1" x 7.5" x 3.5" 23cm x 19cm x 9cm	1.65 lbs 0.75 kgs	10 years

10.31.13

GLOBAL HEADQUARTERS	U.S.	EMEA	CALA	ASIA PACIFIC
Tel: +1(613) 592-2122 Fax: +1(613) 592-4784	Tel: +1(480) 961-9000 Fax: +1(480) 961-1370	Tel: +44(0)1291-430000 Fax: +44(0)1291-430400	Tel: +1(613) 592-2122 Fax: +1(613) 592-7825	Tel: +61(0) 2 9023 9500 Fax: +61(0) 2 9023 9501

FOR MORE INFORMATION ON OUR WORLDWIDE OFFICE LOCATIONS, VISIT OUR WEBSITE AT MITEL.COM/OFFICES

THIS DOCUMENT IS PROVIDED TO YOU FOR INFORMATIONAL PURPOSES ONLY. The information furnished in this document, believed by Mitel to be accurate as of the date of its publication, is subject to change without notice. Mitel assumes no responsibility for any errors or omissions in this document and shall have no obligation to you as a result of having made this document available to you or based upon the information it contains.

M MITEL (design) is a registered trademark of Mitel Networks Corporation. All other products and services are the registered trademarks of their respective holders.

© Copyright 2013, Mitel Networks Corporation. All Rights Reserved.

mitel.com

