Panasonic
ideas for life

KX-UT Series
SIP Telephones

- HD Voice and PoE Enabled
- Two Data Ports* for Simplified Wiring and Connecting a Second Device
- Certified for Use with BroadSoft® BroadWorks®, Digium® Asterisk®, Metaswitch, Brekeke and others
- Power Consumption 1W in ECO Mode*
- Two-year Limited Warranty

*Select models.

2011 INTERNET TELEPHONY PRODUCT OF THE YEAR

BEST OF SHOW 2011 ITEXPO Austin, TX

The Panasonic SIP Phone UT Series

The new, award-winning UT Series combines state-of-the-art telephony with business-friendly features. Choose from entry-level models with large, clear LCDs and conferencing capability to executive desk terminals with 6-line displays and wireless headset compatibility. Designed to yield low total cost of ownership, UT Series phones are PoE enabled and include extra data ports so there's less wiring expense. An energy-saving Eco Mode (select models) lets you reduce power consumption while a powerful two-year limited warranty protects your investment well into the life of the phone.

KX-UT Series Specifications	KX-UT670	KX-UT248-B	KX-UT136-B	KX-UT133-B	KX-UT123-B	KX-UT113-B
LCD Display	Color 262,000	Greyscale Graphical	Monochrome Graphical			
LCD Size	7 inch touchscreen	4.4 inch	242 x 109 pix. – 6 lines	242 x 55 pixels – 3 lines		
LCD Contrast	No	6 levels	6 levels			
LCD Backlight	15/Auto	On/Auto/Off	On/Auto/Off			None
INSTALL OPTIONS						
Desk Mount Tilt	Yes - 2 Positions				No	
Wall Mount	KX-A434-B (optional)	KX-A433-B (optional)			KX-A432-B (optional)	
Power Adaptor	KX-A422 (optional)	KX-A239 (optional)				
NETWORKING						
Ethernet Ports	2 – 10/100/1000		2 – 10/100			1 – 10/100
Power Over Ethernet (PoE)	Yes (Class 3)		Yes (Class 2)			
AUDIO FEATURES						
Audio Codec	G.711, G.722, G.729a	G.711, G.722, G.726, G.729a	G.711, G.722, G.726, G.729a			
Handset, Speaker, Headset Volume	15 levels (includes echo cancellation and distortion prevention)	8 levels (includes echo cancellation and distortion prevention)	8 levels (includes echo cancellation and distortion prevention)			
Ringtones	32					
Ringer Volume	7 levels + Off	6 levels + Off	6 levels + Off			
Headset Port	2.5 mm					
Electronic Hook Switch Control Port	3.5mm Plantronics compatible			None		
Hearing Aid	Compatible with Hearing Aid TIA-1083					
KEYS						
Keys (total[1])	12	41	55	55	31	31
FF Keys	24 (4 pages of 6)	24 (3 pages of 8)	24		-	-
Navigator & Cancel Key	On screen + menu keys	Yes	Yes			
SOFTWARE FEATURES						
Phone Book Entries	Memory Dependent[2]	500 - each with 5 numbers	500 - each with 5 numbers		100 - each with 5 numbers	
Call Log Entries	100 in + 100 out	30 incoming calls + 30 outgoing calls				
Conferencing	3 parties (within terminal – multi-party dependent on server)					
IP FEATURES						
SIP Accounts	6		4		2	
SIP Compatibility	RFC 3261 Standard SIP Server, Asterisk®, BroadSoft®, Metaswitch, Brekeke	RFC 3261 Standard SIP Server, Asterisk®, BroadSoft®, Metaswitch				
IP Version	IPv4					
DHCP Client	Yes					
DNS	Yes					
HTTP/HTTPS	Yes					
SNTP Client	Yes					
VLAN (802.1q)	Yes					
QoS (DiffServ)	Yes					
CONFIGURATION						
Plug & Play Configuration	Server based configuration, TR-069, BroadSoft® Device Management Server					
Manual Configuration	Internal web Configurator, Local (LCD based) network configuration					

1-52 keys include 24 keys, 12 dial keys, 4 soft keys and 12 feature keys. Feature keys include 2 navigation keys (direction and center key).

Design and specifications subject to change without notice.

SIP11129SSr1