

MITEL MiVOICE 5304 IP PHONE



COST-EFFECTIVE ENTRY-LEVEL DISPLAY PHONE

Mitel MiVoice 5304 IP Phone is a cost-effective entry-level display phone that provides access to the features and applications enabled by Mitel's IP-based communications platforms.

This two-line, dual-port IP phone provides users with a 40-character backlit display and supports both Mitel IP (MiNet) and session initiation protocols (SIP).

FEATURE-RICH PHONE WITH SMALL FOOTPRINT

The small footprint of the Mitel MiVoice 5304 IP Phone coupled with the extensive feature set from Mitel's communications platforms make this phone a great fit for enterprise and small- and medium-sized business (SMB) users. It is suitable for places where single-line phones are typically installed such as cafeterias, break rooms, lobbies, and manufacturing floors. The MiVoice 5304 IP Phone is optimized to address the small footprint often required on bedside tables in cruise line cabins, hotel rooms, university dorms, or beside a cash register in retail stores.

The MiVoice 5304 IP Phone is also an ideal classroom phone for both K – 12 and higher education institutions. The phone can be either desk- or wall-mounted depending on the requirements. Teachers and staff are able to make and receive both direct and group pages, access office staff with a single speed dial key, as well as make and receive calls to the classroom. The two-line display delivers calling line ID to the phone, allowing the teacher to see who is calling. The second port allows a PC to be attached to the phone.

FEATURES¹

- Two-line by 20-character backlit display (with auto-dimming)
- Two lines with LED indication: one prime line and one programmable key with LED
- Seven programmable keys: speed dials, features access codes, paging, conferencing, voicemail access etc.
- Twelve-button numeric keypad
- Incoming call visual indication
- Message waiting indication
- Paging and page receive capability
- Direct page and group page support
- Speaker for receiving pages
- Adjustable volume up / down
- Adjustable ringing up / down
- Dual mode: MiNet and SIP support
- V4 Handset (3.4 KHz)
- Wall-mountable (optional)
- Multiple powering options (802.3af compliant)
- ADA compliant (HAC handset)
- Small footprint (26.5 cm x 10cm or 10.5" x 4")
- Designed for power conservation: reduces power consumption for overall energy savings

¹Not all features are supported across all platforms. Refer to the **MiVoice Business, SX-200 ICP**, and **MiVoice Office** collateral for more detailed information.

PROTOCOL SUPPORT

The MiVoice 5304 IP Phone supports SIP and Mitel IP (MiNet) protocols

DUAL PORT

Two 10/100 MB switched Ethernet ports – one connects the MiVoice 5304 IP Phone with an Ethernet wall jack, the other with the user’s PC

POWERING OPTIONS

Accepts standards-based (IEEE 802.3af) power over the LAN and can be powered via a powered switch, a midspan power hub or by local 48 V Ethernet power

POWER ADAPTER (OPTIONAL)

Input: 110 V 50 – 60 Hz or 220V 50 Hz

Output: 48 V DC 250mA LAN PoE
IEEE 802.3af, Class-2 (PoE)

POWER CONSUMPTION

Idle	2.03 W
Typical	2.88 W
Max	3.45 W

ENVIRONMENTAL CONDITIONS

	Temperature	Humidity
Operational	+4°C to +49°C	34% at +49°C 95% at +29°C
Storage	-40°C to +66°C	15% at +66°C 95% at +29°C

SYSTEM SOFTWARE REQUIREMENTS:

- MiVoice Business (formerly Mitel Communications Director) - Release 9.0 (UR1) or later
- MiVoice Office (formerly Mitel 5000 Communications Platform) - Release 3.2 or later
- SX-200 ICP - Release 4.0 (UR5) or later
- MiVoice Border Gateway - Release 5.2 (SP1) or later
- Mitel SIP Software- Release 8.0

REGULATORY STANDARDS

<p>EMC</p>	<p>Canada: ICES-003 (Class B)</p> <p>USA: CFR Title 47, Part 15 (Class B)</p> <p>EU: EN55024 (EU) EN55022 (Class B)</p> <p>Australia / New Zealand: AS / NZS CISPR 22</p> <p>Brazil: Resolution No. 442 / 2006 (Brazil)</p> <p>China: GB9254</p>
<p>Safety</p>	<p>Canada: CSA C22.2 No. 60950-1</p> <p>USA: UL 60950</p> <p>EU: EN 60950 EN 60950-1</p> <p>Australia / New Zealand: AS / NZS 60950-1</p> <p>Brazil: Resolution 238 / 2000 (Brazil)</p> <p>China: GB4943</p>
<p>Telecom</p>	<p>Canada: CS03 Part V (hearing aid compatible)</p> <p>USA: FCC part 68 (CFR 47) (hearing aid compatible)</p> <p>Australia / New Zealand: PTC220 AS / ACIS, S004</p>

5304 IP PHONE SPECIFICATIONS

Voice Traffic	Signaling	Voice QoS	MTBF Rate	Size (L x W x H)	Weight	Compression Support
RTP over UDP	MiNet over TCP SIP	Supports IEEE 802.1p/q for Quality of Service	46 Years	Phone only: 10.5" x 4" x 3.5" (26.7 cm x 10.2 cm x 8.9 cm) Packaged: 11.7" x 6.4" x 3.2" (29.6 cm x 16.2 cm x 8.1 cm)	Phone only: 1.35 lbs or 0.61 kg Packaged: 2.24 lbs or 1.02 kg	G.711, G.729a

GLOBAL HEADQUARTERS	U.S.	EMEA	CALA	ASIA PACIFIC
Tel: +1(613) 592-2122 Fax: +1(613) 592-4784	Tel: +1(480) 961-9000 Fax: +1(480) 961-1370	Tel: +44(0)1291-430000 Fax: +44(0)1291-430400	Tel: +1(613) 592-2122 Fax: +1(613) 592-7825	Tel: +61(0) 2 9023 9500 Fax: +61(0) 2 9023 9501

FOR MORE INFORMATION ON OUR WORLDWIDE OFFICE LOCATIONS, VISIT OUR WEBSITE AT MITEL.COM/OFFICES

THIS DOCUMENT IS PROVIDED TO YOU FOR INFORMATIONAL PURPOSES ONLY. The information furnished in this document, believed by Mitel to be accurate as of the date of its publication, is subject to change without notice. Mitel assumes no responsibility for any errors or omissions in this document and shall have no obligation to you as a result of having made this document available to you or based upon the information it contains.

M MITEL (design) is a registered trademark of Mitel Networks Corporation. All other products and services are the registered trademarks of their respective holders.

© Copyright 2013, Mitel Networks Corporation. All Rights Reserved.

mitel.com

