

Mitel MiVoice 6725 Lync Phone

Maximize the value of your investment in Microsoft Lync

Key Features

- Synchronized integration with Lync desktop client
- Enhanced functionality and call feature control directly from phone
- Color LCD display
- Dual Gigabit Ethernet ports
- Intuitive user interface
- Simple installation and deployment



Embedded in our renowned hardware design is the Microsoft Lync 2010 Phone Edition, offering seamless integration to Microsoft's Lync Server 2010. This combination provides for the fullest Lync feature set available, including simplified installation, management and configuration. The MiVoice 6725 Lync Phone is designed for everyday desktop use and includes dual Gigabit Ethernet ports and message waiting light indicators.

MiVoice 6725 Lync Phone

The MiVoice 6725 Lync Phone is a true IP phone that can operate as a standalone Microsoft Lync endpoint. When connected to a Microsoft Lync 2010 equipped desktop, it provides a synchronized integration with the desktop client, to enable enhanced functionality, such as click-to-dial and desktop control of calling features such as transfer, hold, call park, and conferencing.

The MiVoice 6725 Lync Phone features both a full color 3.5" LCD screen and a separate Unified Communications (UC) presence icon providing direct access to features and presence indicators in Lync. Exceptional voice quality is provided through the use of Microsoft audio codecs in both the handset and hands-free modes.

Key Features and Benefits

"ALWAYS ON" OPERATION

It is no longer necessary to have a phone connected to an operating PC to enjoy the benefits of Lync. The MiVoice 6725 Lync Phone is a true standalone IP phone with Microsoft Lync 2010 Phone Edition embedded in its design. The MiVoice 6725 Lync Phone has the additional advantage of being able to connect to a local desktop PC via a USB cable, enabling desktop PC phone control, multi-media call escalation, and synchronized PC and phone locking.

INTUITIVE INTERFACE

The MiVoice 6725 Lync Phone's efficient and intuitive interface features an ergonomic and user friendly hard key layout, selectable soft keys, a large two-way navigation key, and a 3.5" LCD display screen.

UC PRESENCE INDICATOR

The MiVoice 6725 Lync Phone includes a large presence indicator displaying, at a glance, your own presence status being shown to other Lync users.

SIMPLIFIED DEPLOYMENTS

The MiVoice 6725 Lync Phone is designed to save your business time and money. Dual auto-sensing switched Gigabit Ethernet ports eliminate additional wiring and simplify installations without compromising the bandwidth required by "power users". Integrated IEEE 802.3af Power-over-Ethernet allows easy deployment with centralized powering and backup.

Feature Keys

- Three (3) selectable soft keys
- Headset and speakerphone keys
- RJ headset jack
- Home and back keys
- Message waiting light indicatorOptional customizable hard keys for personalized key configurations
- Two (2) volume keys
- Full numerical keypad (0-9, #, *)

Display and Indicators

- 3.5" QVGA Color Screen LCD
- Intuitive graphical user interface and navigation menus
- Multi-color presence indicator
- Dedicated LED for call and message waiting indicator

Power

- Integrated IEEE 802.3af Power-over-Ethernet (PoE) support
- AC adapter (48V DC) sold separately

Operating Conditions

- Temperature: 0°C to 50°C (32°F to 122°F)
- Relative Humidity: 20% to 90%, noncondensing
- Storage Temperature: -20°C to 70°C (-4°F to 158°F)

Supported Languages*

- English
- Chinese Simplified
- Chinese Traditional
- Danish
- Dutch
- Finnish
- French
- German
- Italian
- Japanese
- Korean
- Norwegian
- Portuguese (Brazil)
- Russian
- Spanish
- Swedish *

Regulatory

CE/EUROPE

- ROHS compliant
- WEEE (2002/96/EC)
- CE Mark (2004/108/EC EMC Directive and 73/23/EEC Low Voltage Directive)

EMC

- FCC Part 15 Class B
- ICES-003 Class B
- EN55022 Class B
- CISPR22 Class B

SAFETY

- CAN/CSA C22.2 No. 60950/ UL 60950-1
- EN 60950
- AS/NZS 60950
- CB scheme

TELECOM/RF

- FCC Part 68 (Hearing Aid Compatibility)

Accessories

- High Angle Stand