



088Z HD



Specifications

General

Frequency Range	VHF: 136~174MHz UHF: 400~470MHz;450-520MHz
Channel Capacity	1024(64 Zones*16 Channels)
Channel Spacing	25kHz/12.5kHz
Frequency Stability	±1.5ppm
Operating Temperature	-25℃~+55℃
Antenna Impedance	50Ω
Operating Voltage	7.5V
Dimensions (H*WxD)	105×60×35mm
Weight (With Antenna & Battery)	225g
Battery	1600mAh

Receiver

Sensitivity	Analog SINAD: 0.22μV/ Digital 5%BER: 0.22μV
Adjacent Channel Selectivity	60dB@12.5kHz/70dB@25kHz
Intermodulation	65dB
Spurious Response Rejection	70dB
Hum and Noise	-40dB@12.5kHz/-45dB@25kHz
Conducted Spurious Emission	≤-57dBm
Audio Response	+1~-3dB
Audio Power	0.8W

Transmitter

RF Power	UHF High Power:4W / Low Power:1W VHF High Power:5W / Low Power:1W
Modulation Limiting	≤2.5kHz@12.5kHz/≤5.0kHz@25kHz
Conducted/Radiated Emission	≤-36dBm(<1GHz)/-30dBm(>1GHz)
Adjacent Channel Power	60dB@12.5kHz/70dB@25kHz
Audio Response	+1~-3dB
Audio Distortion	≤3%
Frequency Stability	±1.5ppm
FM Modulation	25kHz:16KΦF3E / 12.5kHz:11KΦF3E
4FSK Digital Modulation	12.5kHz Data: 7K60F1D and 7K60FXD 12.5kHz Voice: 7K60F1E and 7K60FXE 12.5kHz Voice & Data: 7K60F1W

Digital Vocoder Type

AMBE+2™

Digital Protocol

ETS1 TS 102 361-1,-2,-3

All specifications are tested according to applicable standards and subject to changes without notice due to continuous development.



HQT Digital Series
DH-2880



Main Features

- **High Cost Performance**
HQT DH-2880 is a professional digital portable radio which is reliable and safe. Its ergonomic design makes it easy to carry and hide.
- **Dual Modes (Analog + Digital)**
DH-2880 can operate in either analog or digital mode. It is compatible with the prevalent analog system, ensuring a smooth analog-to-digital transition.
- **Maximum Efficiency**
DH-2880 adopts TDMA technology which ensures high-efficient frequency coverage and control mode of RF power, and its battery life is 40% longer when it is operated in digital mode than that in analog mode.
- **Better and Clearer Communication**
DH-2880 adopts digital technologies which effectively control background noise and squelch during voice transmission, so that it can transmit clear and desired voice.
- **Secure Communication**
DH-2880 can control the selection of RX contact or RX group of voice in digital mode. Every DH-2880 has a unique ID, which enables users to do one-to-one conversation which will not be received by others. Besides, it supports digital voice encryption in digital mode.

- VOX
- Voice Prompts
- Channel Scan
- Emergency Alarm
- Programmable Key
- TOT (Time Out Timer)
- Upgradeable Software
- Dual Modes (Analog + Digital)
- Signaling: DTMF Encode, QT/DQT
- Voice Call Types: Private Call, Group Call and All Call
- Radio Disable, Radio Enable, One Touch Call, Remote Monitor

Accessory List

Standard Accessories			
Antenna	Battery	Charge Adapter	Hand Strap
Desktop Charger		Belt Clip	
Optional Accessories			
Earphone	Remote Microphone	Programming Cable	Clone Cable

SHENZHEN HQT SCIENCE & TECHNOLOGY CO.,LTD.
 TEL: + 86-755-86028800
 E-mail: hqt@hqtsolutions.com
 ADD:5/F, East of Building M-8, Central Zone, Hi-tech Industrial Park,
 Nanshan District, Shenzhen, P.R.C. 518057



www.hqtsolutions.com

Your Local Dealer

All rights are reserved to HQT. Pictures shown in this brochure are for your reference only. All specifications and descriptions are subject to change without notice.