

Mitel MiVoice 5603 Wireless Phone

Key Features

- Enhanced, customizable Graphical User Interface (GUI)
- High quality voice transmission
- Large illuminated Black / White and greyscale display
- MiVoice Business Management Integration



In office, education or retail environments, the requirement for fast, easy and clear communication is an integral part of operations. Designed for flexibility and low cost, the MiVoice 5603 Wireless Phone provides an advanced, user-friendly interface. The MiVoice 5603 Wireless Phone provides value for the user who has less complex demands, but who still requires a quality handset for intense daily use.

In addition to enhanced MiVoice Business feature interworking over SIP, this IP-DECT handset can be twinned to a user's desktop in conjunction with their MiVoice Business Personal Ring Group capability, allowing single number reachability, regardless of a user's location. The MiVoice 5603 Wireless Phone comes with a default list of MiVoice Business features preprogrammed.

MiVoice Business Management Integration

The MiVoice 5603 Wireless Phone is configured as a specific device type on the MiVoice Business communications platform, making adds, moves and changes is simple to manage from the MiVoice Enterprise Manager.

Simplified Device Management

The Mitel IP-DECT System (Global) software release 4.0 introduced support for simplified device management, compatible with the MiVoice 5603 Wireless Phone. Programming can be achieved over-the-air via the Mitel Wireless Services Messaging Gateway, or via a PC in conjunction with the MiVoice 5603 / 5604 / 5607 Wireless Phone Programmer. This includes both programming and software upgrading.

KEY FEATURES:

- Enhanced, customizable Graphical User Interface (GUI)
- High quality voice
- Large illuminated Black / White and greyscale display
- Local phonebook (500 entries)
- Central phonebook
- Call list with 25 last calls
- Speakerphone mode
- Vibrating ring
- Six languages and one customizable
- Standard (2.5mm) headset connector
- Central Management support
- Battery Life (talk / standby): 16 hrs / 180 hrs
- Manual and automatic keypad lock
- GAP / CAP compliant DECT handset
- Enterprise grade enclosure (IP40 classification)

Optional Accessories

- MiVoice 5603 / 5604 Wireless Phone Desktop Charger (charges one handset)
- MiVoice 5603 / 5604 / 5607 Wireless Phone Desktop Programmer (charges and programs one handset)
- MiVoice 5603 / 5604 / 5607 / 5624 Wireless Phone Rack Charger (charges up to six handsets)
- Leather Case
- Clips: Swivel type, Hinge type
- Security Cord
- Headset: with Microphone on Boom

Technical Specifications

PHYSICAL

Size (L X W X D)	Weight	Material	Color	Display (W X H)	Clip
» 133 x 53 x 24 mm (5.27 x 2.09 x .94 in.)	» 115 g (battery and clip included)	» Case: PC-ABS, Key pad: Silicone, Clip: POM	» Black	» 28 x 35 mm (1.10 x 1.38 in) FSTN B / W	» Hinge type (standard) or swivel type

BATTERY AND CHARGING

Type	Speech Time	Stand-By Time	Charge Time	Discharge / Charge Cycles
» 600 mAh (Li-Ion)	» 16 hours (optimal)	» 180 hours (optimal)	» < 4 hours	» >=65% capacity left after 500 full charge / discharge cycles

LANGUAGES

Six preinstalled (English, French, Dutch, German, Russian, Spanish). One additional programmable. 12 languages available for download (Czech, Danish, Finnish, Greek, Hungarian, Italian, Norwegian, Portuguese, Polish, Slovakian, Swedish, and Turkish)

CENTRAL PHONEBOOK

Maximum name and number length: 40 characters / name, 20 digits / number

LOCAL PHONEBOOK

Storage of contacts	Entries
» 48 character name » 24 digit work number » 24 digit mobile phone number » 24 digit other numbers	» 250 editable or 500 programmed

TELEPHONY

Indication	Answer Call Options	Call List Storage Capacity
» 14 ring signals, flashing LED and vibrator	» Button press or auto answer	» 25 calls (received, dialed and missed) with time stamp

ENVIRONMENTAL

Operating Temperature	Storage Temperature	Enclosure Protection	Immunity to Electromagnetic Fields	Immunity to ESD	Free Fall Test, Standard Product
» 0°C to +40°C (32°F to 104°F)	» -20°C to +60°C (-4°F to 140°F)	» IP40, IEC EN60529	» 3 V/m EN61000-4-3	» 4 kV contact discharge and 8 kV air discharge (EN61000-4-2)	» IEC 60068-2-32, procedure 1, dropped 12 times from 1 meter

AUDIO

Ring Signal	Earpiece	Maximum Sound Pressure Level	Loudspeaker
» Adjustable in 8 steps	» Adjustable in 8 steps of 3dB each	» 88 dBA at 10 cm	» Duplex loud speaking function

CONNECTORS

Multi-Purpose Connector	Headset Connector
» For battery charging, software download, and configuration	» Standard 2.5 mm

USER INTERFACE

Display (W X H)	Indicator	Vibrator	Keypad
» 112 x 115 pixels with white LED backlight	» LED on top / front for visual indication of incoming call, and charging	» Incoming call	» Soft keys » SHook off key » SOn hook and Power On / Off on the same key » SFour way navigation key » SNumerical keys

RADIO

Compliance to DECT standard

System Requirements

- MiVoice Business – Release 4.1 or later (formerly Mitel Communications Director)
- MiVoice Office – Release 6.0 or later (formerly Mitel 5000 Communications Platform)
- MiVoice Border Gateway – Release 7.1