

Performance with flexibility

Our latest terminal provides GSM voice communications within coverage of a cellular wireless network. With both a landline and GSM connection, the T400LR provides a number of capabilities including landline backup and least cost routing.

With its excellent voice quality, affordability, compact size, the Burnside T400LR is designed to operate in a wide range of installation environments. Four supplied NiMH AA cells provide uninterrupted service for over 50 hours standby and up to 5 hours talk-time in the event of a mains power failure.

T400LR Main Features

- High performance, high quality configurable fixed cellular terminal
- Dual band GSM for EU voice calls
- Automatic selection of GSM if landline fails
- Least cost routine for outgoing calls to mobiles
- Call progress announcements (CPA)
- CLI (Caller Display) information presented to a connected telephone
- Can be configured by dial codes or remotely by SMS
- Built-in battery backup using high quality Panasonic NiMH AA cells
- Long life battery technology .
- Easy and quick to install
- Energy efficient design for low running cost
- Relay for pass-through from FXO to FXS after battery exhaustion
- SMS reporting of terminal status
- Programmable configuration for regional tone compatibility
- Designed for long service life and product safety
- SMA connector for connecting supplied high performance antenna

Burnside Telecom is a UK designer and manufacturer of innovative fixed cellular terminals, wall mounted mobile phones and help points. Our products are currently used in 19 countries across the globe by customers including multinational companies, mobile network operators, government departments, local authorities and security services.



Typical T400LR Applications

Anyone wanting to connect a standard telephone to the mobile phone network.

Telecare and domestic alarms
Mobile Network Operators
Remote communications
Facilities management
Exhibitions and events

Burnside Telecom Ltd

Sturminster Newton
Dorset
United Kingdom

Phone: +44 (0)1258 919112
E-mail: sales@burnsidetelecom.com
Web site: www.burnsidetelecom.com

Model T400LR - Technical Data

T400LR Specifications

Feature	Description
GSM Bands	Dual-band GSM phase 2/2+ 900/1800 MHz
Speech Communication	Codec for HR, FR, EFR and AMR EFR & FR may be selected for Telecare applications
Configuration	May be programmed by dial codes and SMS commands: Automatic one-number dial Various call control options including call duration limit
In-call Features	Recall (flash hook) with keycodes supports call waiting, multi-party calls and explicit call transfer
Telephone Interface (FXS)	Connector: RJ11 or BT431A socket (depending on model) Any type of corded or cordless touch tone DTMF phone DC loop current 25mA (20mA or 30mA, selectable) Ringing Signal 25Hz sinusoidal 43V RMS Choice of call progress tone cadences Ringing load 3 REN CLI sent to phone with time and date: UK, ETSI and Bellcore
PSTN interface (FXO)	Relay bypass for power failure after battery exhaustion Real time on hook voltage measurement Off-hook voltage and current measurement Isolated to 3kV
Indicators	3 x LEDs: Battery Charging, Battery Low, Searching, PIN, Weak Signal, Incoming Call, Call in Progress, Fault
External antenna port	Connector: 50 ohm SMA male
Antenna (supplied)	High performance compact hinged type
Power	12VDC via 2.1mm barrel connector Standby: 0.1W, In call: 1.9W average Supplied AC adaptor 100 - 240VAC 50-60Hz
Battery Backup	Four NiMH rechargeable AA cells Over 50 hours standby or up to 5 hours talk-time
Case	Wall mountable, ABS UL V0 Dimensions: 141 x 91 x 40mm, Boxed: 173 x 104 x 100mm
Weight	Unit standalone : 325g / Boxed: 615g
Temperature Range	Normal Operation: -20°C to +40°C Charging: 0°C to +40°C, Storage: -40°C to +55°C
Approvals	CE, local approvals, RoHS, Reach & WEEE



Rear of UK version



Base shows T00FX, T400LR is the same



Standard T400LR Kit Versions

Part No.	Description and kit contents
722179	T400LR UK Terminal pack Containing: 1 x 328034 FCT 1 x 268029 Antenna 4 x Panasonic NiMH AA cells 1 x 778017 UK AC Adapter 1 x 225032 PSTN cable 1 x Quick start guide
722180	T400LR EU Terminal pack Containing: 1 x 328035 FCT 1 x 268029 Antenna 4 x Panasonic NiMH AA cells 1 x 778018 EU AC Adapter 1 x 225034 PSTN cable

Supplied by: