





Windows Hello compatible webcam with built-in privacy lens cover



Universal 1080p HD 30fps webcam

Ideal for use where office security is essential

Ease of access to your device with Windows Hello facial recognition

Plug & play solution - No software or downloads needed

96° Field of view

Dual stereo full duplexed microphones for smooth natural conversations

Built-in privacy lens cover

Built-in camera in-use LED indicator

USB Type-A and USB Type-C connectivity included

Multi-angled desk mount / monitor mount (as well as tripod fixing screw option on the base) giving full 360° camera rotation and 90° camera forward tilt

2 year standard repair or replacement warranty









Windows Hello compatible USB webcam with a full HD 1080p glass lens, built-in privacy lens cover, USB-A and USB-C connectivity to allow optional connection to any USB-A or USB-C device.

Compatible with all major softphones.

Plug & play solution - No additional software or downloads needed.











1080p 30 fps

Compatible with

Undistorted

Integrated USB-A / USB-C to

Overview

Features	HD 1920 x 1080p Camera	
	Full HD 1080p glass lens - No optical distortion	
	Built-in privacy lens cover	
	Two full duplexed microphones - Built in dual stereo	
	Built-in camera in-use LED indicator	
	USB 2.0 Type-A and USB-C connectivity	
	Desk mount, monitor mount and universal thread for tripod option	
	Full 360° camera rotation including 90° tilt for over desk viewing	
	Automatic low-light correction	
	AEC – Automatic Echo Cancellation	
	ANS – Automatic Noise Suppression	
Certifications	UKCA, CE, FCC, RoHS, REACH	
Unit Dimensions	92.5 x 52 x 31 mm	
Warranty	24 Month repair or replacement warranty	
MOQ	Master Shipping Carton: 40	
SKU:	575-400-001	
EAN:	5060126959786	

Technical Data

IR Camera SENSOR:	Sensor Type	1/9"CMOS
	Array Size	1280*720 30FPS
	Pixel Size	1.4 μm x 1.4 μm / BSI
RGB Camera SENSOR:	Sensor Type	1/2.9" CMOS
	Array Size	1920*1080P 30FPS
	Pixel Size	2.8µm*2.8µm FSI
IR Lens:	Construction	3P
	IR Filter	850nm
	FOV	D=85±°;
	F/No	2.4±5%
	TV Distortion	<-2.6%
RGB Lens:	Construction	1G4P+IR
	IR Filter	650nm
	FOV	D=96±°
	F/No	2.5±5%
	TV Distortion	<-0.9%
MIC:	Dimensional	Ø4.0*1.5mm
	Sensitivity	-38±3db
	S/N ratio	60db
	Pick-up distance	3m
Temperature(Operation)	-10°c to 60°c	
Temperature(Storage)	-10°c to 60°c	
USB Power Supply Voltage	DC 5V	
Interface	USB 2.0 USB-A/TYPE-C	
Operating System Request	Windows 10-11 (Windows Hello	
AGE/AEC/White Balance	Auto	
Supports compression form	MJPEG/YUV	