

Mitel 6910 IP Phone

The ideal option for businesses who need a modern and reliable office phone for standard communications.

Key Features

- 3.4" 128x48 pixel LCD display with soft white backlighting
- HD wideband audio
- Eight programmable personal keys with LED indicator
- 4-way navigation key with Select/OK button
- Dual Gigabit Ethernet ports
- Native EHS/DHSG headset support
- PoE Class 2



The Mitel 6910 IP Phone offers exceptional quality and standard telephony functions in an enterprise grade IP desktop phone. The Mitel 6910 features Dual Gigabit Ethernet ports and a large 3.4" LCD display with soft white backlighting and large fonts, making the screen easy to read in any lighting condition. With eight programmable keys, native DHSG/ EHS analog headset support, and high definition audio quality, the Mitel 6910 IP Phone is ideal for business of all sizes.

Remarkable Audio

The Mitel 6910 IP phones feature high definition audio technology to deliver enhanced performance and voice clarity. Integrating HD wideband audio codecs, advanced audio processing and hardware components that support a true wideband frequency range, the 6910 offers a superior voice experience on each audio path – handset, speakerphone or headset port – making conversations crystal clear and more life-like.

Flexible Headset Options

The Mitel 6910 IP Phone features an innovative headset port that uniquely provides support for wired analog headsets with or without Electronic Hook Switch (EHS/DHSG). Users with wireless headsets that support EHS/DHSG can connect directly to the 6910 using available third-party cables.

Enhanced Call Management

With an extensive array of supported features including directory, calls logs, voicemail and eight programmable keys, the Mitel 6910 IP Phone is designed for easy access to all the most frequently used call management features.

Feature Keys

- 8 Programmable Personal keys with LEDs for Call Appearances and, Speed Dials
- 4-way navigation key with Select/OK button
- Dedicated function keys, including Conference, Transfer, Contacts, Call History, Voicemail, Hold, Redial, Goodbye, Options, Volume Up/Down key, Mute (with LED) and Speaker/Headset (with LED)

Audio and Codecs

- Mitel Hi-Q Audio Technology
- Hearing aid compatible (HAC) handset
- Full-duplex speakerphone
- Wideband handset and speakerphone
- Codecs: G.711 μ -law / A-law, iLBC, G.722, G.726, Linear 16, G.729
- EHS/DHSG and 4-pin modular analog headset supported

Display and Indicators

- 3.4" 128x48 pixel graphical display
- Soft white backlight for user comfort in any lighting condition
- Call and message waiting indicator
- 8 Programmable Personal key indicators (single color)
- Speaker/Headset & Mute State Indicators

Protocol Support

- Mitel IP (Minet) protocol support
- SIP (Session Initiation Protocol) Support

System Software Requirements

- MiCloud Connect

Integration and Connectivity

- Dual 10/100/1000 Mbps Ethernet ports (LAN/PC)
- Support for use with Mitel Connect Client
- Multiple-languages support: English, French, German, Spanish, Dutch
- Secure encrypted voice communication
- Quality of Service support – IEEE 802.1 p/Q VLAN and priority tagging
- IEEE 802.1x authentication support
- Dedicated 4-pin RJ9 modular headset port convertible to EHS/DHSG capable headset port

Powering

- PoE Class 2 or DC via option power supply
- Level "V" energy efficiency rated power adapters available

Environmental / Regulatory Standards

- Operational:
 - » Operational +4°C to +49°C
 - » Humidity 34% at +49°C 95% at +29°C
- Storage:
 - » Operational -30°C to +70°C
 - » Humidity 15% at +70°C 95% at +29°C

EMC

- Canada: ICES-003 (Class B)
 - Rss-247
- USA: CFR Title 47, Part 15 (Class B)
 - FCC Part 15 Subpart C
- European Union: EN55024 (EU)
 - EN55032 (Class B)
 - EN 301-489-1-17
 - EN300 328
 - EN 50360
- Australia / New Zealand: AS / NZS
CISPR 22

Safety

- Canada: CSA C22.2 NO. 60950-1
- USA: UL 60950-1
- European Union: EN 60950-1
- Australia / New Zealand: AS / NZS 60950 - 1

Other

- Size (L x W x H): 8.9 in x 5.9in x 7.5 in
(22.5cm x 15cm x 19cm)
- Weight: 2.2 lbs. or 0.98 kg

**Feature support may not be applicable to all solutions*